

TPS-221-3020GB

电子花样机 (300mm x 200mm)

ELECTRONIC PATTERN SEWING MACHINE



- 触摸式操作控制盘
Touch screen panel
- 无油式针杆清洁缝纫
Oil-free needle bar ;Clean sewing
- 操作简易，定位简单、精确
Simple operation,easy positioning ,accurate
- 独特的面线夹持功能
Unique upper thread holding device
- 新型的拉杆式松线装置(已申请国家专利)
New pulling thread-slacking device (which has been applied for the national patent)





适用于鞋类、箱包、衬衫袖口等的缝制；是一款中型缝制范围应用较广泛的机型，具有生产性、经济性都更有竞争力产品；比一般传统缝制方式生产力可提高100%~300%左右。

It is suitable for shoes ,bags and cuff of t-shirts.With medium sewing area and extensive usage ,it is competitive in productivity and economy ,which improves productivity to 100%-300%.

三工位旋转式工作台（选购）

Three working location rotating table(optional)

- 适用于多品种小批量多层组合模板；
Applied for layers of combined model plates in various kinds with small batch.
- 缝制与装夹同步，消除人员/机台等待的时间浪费，提高工作效率；
Clamping and sewing simultaneously, the machine reduces the time wasted on waiting and improves working efficiency.
- 自动对位、自动扫描启动缝制花样；
Automatically start after automatic positioning and model plate scanning.
- 可连续自动切换多种花样；
Successive and automatic program shifting.
- 可实现同一面料上多层次组合花样同一机台连续缝制来缩短生产周期。
Sewing layers of combined patterns in same fabric, this device reduces the producing period by using same table&stand.



型号 Model	平缝 Flat Seam	2倍旋梭 2-time hook	缝纫面积 Sewing area	针距 Stitch length	切线装置 Cutting device	扫线装置 Scavenging device	最高缝纫速度 Highest sewing speed	气压 Air pressure
TPS-221-3020GB-01/02A	★	★	300 × 200mm	0.05 - 12.7mm	★	★	2,700 rpm	1.8 L/min

型号 Model	TPS-221-3020GB-01A(厚料Thick material)	TPS-221-3020GB-02A(中厚料Medium-heavy material)
线迹Line	单针平缝 / Sing-needle flat seam	
最高缝纫速度Highest sewing speed	2,700 rpm	
缝制区域Sewing area device	最大Max. 300 × 200mm	
送布方式Cloth feeding mode	间歇送布（脉冲马达驱动方式）/Intermittent feeding（Pulse motor drive mode）	
针距长度Stitch length	0.05-12.7mm	
最大针数Max. needles number	20,000针/1个图案 / (20,000 needles/1 pattern)	
可储存针数Maximum stitching amount	内置内存可储存500000针/500000 stitch can be stored in build-in memory	
压脚驱动方式Presser foot driving method	A-气动Pneumatic	
压脚高度Work clamp height	最大Max. 30mm	
两步压脚 2- step presser foot	一体式压脚/All-in-one presser foot	
大压脚高度 High pressure foot height	最大Max. 30mm	
大压脚形式Work clamp shape	一体式压脚/All-in-one presser foot	
间歇压上升量 Rising amount by intermittent foot presser	22mm	
间歇压上行程 Stroke by intermittent presser foot	0或2-10mm（出厂设置：3mm）0 or 2-10mm（Factory defaults: 3mm）	
扫线装置Scavenging device	标准装备/Standard facility	
切线装置Cutting device	标准装备/Standard facility	
用户程序数Customer program amount	50	
循环程序数 Recycling program amount	9	
马达Motor	AC伺服马达550W直接驱动式 / AC servomotor 550W	
重量Weight	机头：约150kg/Head: About 150kg	
电源Power	单相Single phase 100~120V、200~240V、三相3-phase 200~240V、380~415V、350V	
气压Air pressure	0.5Mpa、1.8L/min	

以上型号仅供参考，详细情况请咨询当地经销商。
The above types are only for reference, and you can consult local distributors for details.

为了改良，产品规格若有变更，恕不另行通知。为安全起见，使用之前，请仔细阅读使用手册。
Specifications are subject to change for improvement without further notice. Please carefully read the operating manual before use for safety.

西安鹰高进出口有限公司
TOPEAGLE INTERNATIONAL LTD.



地址：西安市高新区丈八二路31号逸翠尚府北区1栋4单元1201室
电话：+86-29-68723798 / 68829612
传真：+86-29-68723818
邮箱：sale@eagleco.cn
网址：www.topeaglesewing.com
邮编：710065

Add: 4-1201, Block 1, No.31 Zhangba Er Road, Xi'an, China-710065
Tel: +86-29-68723798 / 68829612
Fax: +86-29-68723818
E-mail: sale@eagleco.cn
Web: www.topeaglesewing.com